

No.MTH.001CPR2013-07-01

- Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with water absorption E_b >10 %
- 2. Intended use(s)

For internal wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

- Name and identification number of notified laboratory, if relevant not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue
- 6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	EN 14411:2012
Bond strength/adhesion, for:		EN 14411:2012
Cementitious adhesive, type C1	>0,5 N/mm ²	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2021

Place and date of issue

Signature



No.MTH.002CPR2013-07-01

Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with water absorption 3%< E_b ≤ 6%

2. Intended use(s)

For internal floorings

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

Name and identification number of notified laboratory, if relevant – not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL}	
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 000 N	EN 14411:2012
Slipperiness	NPD	
Tactility	NPD	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2021

Place and date of issue

Signature

14 CERAMICA
SCUTIOTI S LU

1 COS SIVAIN



No.MTH.003CPR2013-07-01

- Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with low water absorption E_b ≤0,5 %
- 2. Intended use(s)

For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

- Name and identification number of notified laboratory, if relevant not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue
- 6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 300 N	
Slipperiness	NPD	
Tactility	NPD	EN 14411:2012
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	> 1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2021 Place and date of issue Signature

All CERAMINA
SOUTHORS SU

SOCOTIVO DE LES DE LE



No.MTH.004CPR2013-07-01

Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with water absorption 0,5%< E_b ≤ 3%

2. Intended use(s)

For internal floorings

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

Name and identification number of notified laboratory, if relevant – not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL}	
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 100 N	EN 14411:2012
Slipperiness	NPD	
Tactility	NPD	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2021

Place and date of issue

Signature



No.MTH.006CPR2013-07-01

Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with water absorption 0,5%< E_b ≤ 3% with thickness < 7 mm</p>

2. Intended use(s)

For internal flooring and walling

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

Name and identification number of notified laboratory, if relevant – not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL}	
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 700 N	EN 14411:2012
Slipperiness	NPD	
Tactility	NPD	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2021

Place and date of issue Signature

TALL CERAMICA SOLUTIONS, S.L.U COramida CIF B-12959112 Cayle Del Toll, nº 18 12200 ONDA (CASTELLÓN) SPAIN



No.MTH.007CPR2013-07-01

Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with low water absorption E_b ≤0,5 % with thickness < 7,5 mm.

2. Intended use(s)

For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 3 and 4

Name and identification number of notified laboratory, if relevant – not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	
Release of dangerous substance, for:		
- Cadmium	< 0,01 mg/l	
- Lead	< 0,1 mg/l	
Breaking strength	> 700 N	
Slipperiness	NPD	
Tactility	NPD	EN 14411:2012
Bond strength/adhesion, for:		
Cementitious adhesive, type C2 E S2	> 1 N/mm²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2023 Place and date of issue TAU CERAMICA SOLUTIONS, S.L.U. CIF B-12958112 CASTELLON) SPAIN



No.MTH.008CPR2013-07-01

1. Unique identification code of the product type

Type, batch or serial number or any other element allowing identification of the product

Dry-pressed ceramic tiles, with low water absorption $E_b \le 0.5 \%$, with thickness $\ge 7.5 \text{ mm meshed}$.

2. Intended use(s)

For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 3 and 4

 Name and identification number of notified laboratory, if relevant – not applicable Task(s) carried out

AVCP system

Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0	
Release of dangerous substance, for:	, ,	n,
- Cadmium	< 0,01 mg/l	
- Lead	< 0,1 mg/l	
Breaking strength	> 1300 N	
Slipperiness	NPD	
Tactility	NPD	EN 14411:2012
Bond strength/adhesion, for:		
Cementitious adhesive, type C2 E S2	> 1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2023 Place and date of issue JAU CERAMICA SOLUTIONS, S.L.U. CIF B-12958112 Callé Del Toll, nº 18 12200 ONDA (CASTELLON) SPAIN



No.MTH.009CPR2013-07-01

Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with low water absorption E_b ≤0,5 %, with thickness ≥ 7,5 mm meshed.

2. Intended use(s)

For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 3 and 4

Name and identification number of notified laboratory, if relevant – not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0	
Release of dangerous substance, for:		
- Cadmium	< 0,01 mg/l	
- Lead	< 0,1 mg/l	
Breaking strength	> 1300 N	
Slipperiness	NPD	
Tactility	NPD	EN 14411:2012
Bond strength/adhesion, for:		
Cementitious adhesive, type C2 E S2	> 1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager)

Name and function

Onda, 01-01-2023 Place and date of issue TAU CERAMICA SOLUTIONS, S.L.U. CORONICO GIGNATURE B-12958112
Calle Del Toll, nº 18
12200 ONDA CASTELLÓN SPAIN



No.MTH.010CPR2013-07-01

Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product

Dry-pressed ceramic tiles, with low water absorption $E_b \le 0.5 \%$, with thickness $\ge 7.5 \text{ mm.}$

2. Intended use(s)

For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 3 and 4

Name and identification number of notified laboratory, if relevant – not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	
Release of dangerous substance, for:		
- Cadmium	< 0,01 mg/l	
- Lead	< 0,1 mg/l	-
Breaking strength	> 1300 N	
Slipperiness	NPD	
Tactility	NPD	EN 14411:2012
Bond strength/adhesion, for:		
Cementitious adhesive, type C2 E S2	> 1 N/mm ²	*
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager)

Name and function

Onda, 01-01-2023 Place and date of issue

TAU CRAINCA SOLUTIONS, S.L.V. CONTOURNE CONTOU

Signature