No.MTH.001CPR2013-07-01



- 1. Unique identification code of the product type
  Type, batch or serial number or any other element allowing identification of the product

  Dry-pressed ceramic tiles, with water absorption  $E_b > 10 \%$
- 2. Intended use(s)

#### For internal wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

- 4. System(s) of assessment and verification of constancy of performance (AVCP)

  Systems 4
- Name and identification number of notified laboratory, if relevant not applicable
   Task(s) carried out
   AVCP system
   Document issued and date of issue
- 6. Declared performances

| Essential characteristics            | Performance            | Harmonised technical specification |
|--------------------------------------|------------------------|------------------------------------|
| Reaction to fire                     | A1                     |                                    |
| Release of dangerous substance, for: |                        |                                    |
| - Cadmium                            | NPD                    |                                    |
| - Lead                               | NPD                    | DO EN 4444 0040                    |
| Bond strength/adhesion, for:         |                        | BS EN 14411:2012                   |
| Cementitious adhesive, type C1       | >0,5 N/mm <sup>2</sup> |                                    |
| Durability for:                      |                        |                                    |
| - internal use:                      | Pass                   |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2021

Place and date of issue

1.AU CERAMICA SOLUTIONS, ALLU CERAMICA SOLUTIONS, ALLU CERAMICA CASTELLON) SPAIN





- 2. Intended use(s)

## For internal floorings

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

- System(s) of assessment and verification of constancy of performance (AVCP)
   Systems 4
- Name and identification number of notified laboratory, if relevant not applicable Task(s) carried out AVCP system

Document issued and date of issue

6. Declared performances

| Essential characteristics            | Performance      | Harmonised technical specification |
|--------------------------------------|------------------|------------------------------------|
| Reaction to fire                     | A1 <sub>FL</sub> |                                    |
| Release of dangerous substance, for: |                  |                                    |
| - Cadmium                            | NPD              |                                    |
| - Lead                               | NPD              |                                    |
| Breaking strength                    | > 1 000 N        | BS EN 14411:2012                   |
| Slipperiness                         | NPD              |                                    |
| Tactility                            | NPD              |                                    |
| Durability for:                      |                  |                                    |
| - internal use:                      | Pass             |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2021

Place and date of issue

Signature

TAU CERAMICA SOLUTIONS, S.L.U. CIF B-12958112

Caramica Calle Del Toll, nº18 12200 ONDA (CASTELLON) SPAIN



No.MTH.003CPR2013-07-01

- Unique identification code of the product type
   Type, batch or serial number or any other element allowing identification of the product
   Dry-pressed ceramic tiles, with low water absorption E<sub>b</sub> ≤0,5 %
- 2. Intended use(s)

# For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

- 4. System(s) of assessment and verification of constancy of performance (AVCP)

  Systems 4
- Name and identification number of notified laboratory, if relevant not applicable
   Task(s) carried out
   AVCP system
   Document issued and date of issue
- 6. Declared performances

| Essential characteristics              | Performance           | Harmonised technical specification |
|--|-----------------------|------------------------------------|
| Reaction to fire                       | A1 <sub>FL</sub> /A1  |                                    |
| Release of dangerous substance, for:   |                       |                                    |
| - Cadmium                              | NPD                   |                                    |
| - Lead                                 | NPD                   |                                    |
| Breaking strength                      | > 1 300 N             |                                    |
| Slipperiness                           | NPD                   |                                    |
| Tactility                              | NPD                   | BS EN 14411:2012                   |
| Bond strength/adhesion, for:           |                       |                                    |
| Cementitious adhesive, type C2         | > 1 N/mm <sup>2</sup> |                                    |
| Thermal shock resistance               | Pass                  |                                    |
| Durability for:                        |                       |                                    |
| - internal use:                        | Pass                  |                                    |
| - external use: freeze-thaw resistance | Pass                  |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2021

Place and date of issue







- Unique identification code of the product type
   Type, batch or serial number or any other element allowing identification of the product
   Dry-pressed ceramic tiles, with water absorption 0,5%< E<sub>b</sub> ≤ 3%
- 2. Intended use(s)

## For internal floorings

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

- 4. System(s) of assessment and verification of constancy of performance (AVCP)

  Systems 4
- Name and identification number of notified laboratory, if relevant not applicable
   Task(s) carried out
   AVCP system
   Document issued and date of issue
- 6. Declared performances

| Essential characteristics            | Performance      | Harmonised technical specification |
|--------------------------------------|------------------|------------------------------------|
| Reaction to fire                     | A1 <sub>FL</sub> |                                    |
| Release of dangerous substance, for: |                  |                                    |
| - Cadmium                            | NPD              |                                    |
| - Lead                               | NPD              |                                    |
| Breaking strength                    | > 1 100 N        | BS EN 14411:2012                   |
| Slipperiness                         | NPD              |                                    |
| Tactility                            | NPD              |                                    |
| Durability for:                      |                  |                                    |
| - internal use:                      | Pass             |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2021

Place and date of issue

Signature

TAU CERAMICA SOLUTIONS, S.L.U. CER B-12988112 Cafle Del Toll, nº 18 12200 ONDA (CASTELLÓN) SPAIN





Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with water absorption 0,5%< E<sub>b</sub> ≤ 3% with thickness < 7 mm</li>

2. Intended use(s)

## For internal floorings

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

 Name and identification number of notified laboratory, if relevant – not applicable Task(s) carried out AVCP system

Document issued and date of issue

#### 6. Declared performances

| Essential characteristics            | Performance      | Harmonised technical specification |
|--------------------------------------|------------------|------------------------------------|
| Reaction to fire                     | A1 <sub>FL</sub> |                                    |
| Release of dangerous substance, for: |                  |                                    |
| - Cadmium                            | NPD              |                                    |
| - Lead                               | NPD              |                                    |
| Breaking strength                    | > 700 N          | BS EN 14411:2012                   |
| Slipperiness                         | NPD              |                                    |
| Tactility                            | NPD              |                                    |
| Durability for:                      |                  |                                    |
| - internal use:                      | Pass             |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda. 01-01-2021

Place and date of issue

Signature

RAMICA

SOLUTIONS, S.L.U.
CRAMICOL
CIF B 12958112
Calle pel Toll, ny 18
12200 ONDA (CASTELLON) SPAIN





Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with low water absorption E<sub>b</sub> ≤0,5 % with thickness < 7,5 mm</p>

2. Intended use(s)

#### For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

## TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 3 and 4

Name and identification number of notified laboratory, if relevant – not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

#### 6. Declared performances

| Essential characteristics              | Performance           | Harmonised technical specification |
|--|-----------------------|------------------------------------|
| Reaction to fire                       | A1 <sub>FL</sub> /A1  |                                    |
| Release of dangerous substance, for:   |                       |                                    |
| - Cadmium                              | < 0,01 mg/l           |                                    |
| - Lead                                 | < 0,1 mg/l            |                                    |
| Breaking strength                      | > 700 N               |                                    |
| Slipperiness                           | NPD                   |                                    |
| Tactility                              | NPD                   | BS EN 14411:2012                   |
| Bond strength/adhesion, for:           |                       |                                    |
| Cementitious adhesive, type C2         | > 1 N/mm <sup>2</sup> |                                    |
| Thermal shock resistance               | Pass                  |                                    |
| Durability for:                        |                       |                                    |
| - internal use:                        | Pass                  |                                    |
| - external use: freeze-thaw resistance | Pass                  |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2023 Place and date of issue TAU CERAMICA SOLUTIONS, S.L.U. CUrcurus gnature | B-12958112 Calle Del Toll, 1º 18 12200 ONDA (CASTELLON) SPAIN





 Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with low water absorption E<sub>b</sub> ≤0,5 % with thickness ≥ 7,5 mm meshed.

2. Intended use(s)

#### For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

# TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

#### Systems 3 and 4

Name and identification number of notified laboratory, if relevant – not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

## 6. Declared performances

| Essential characteristics              | Performance           | Harmonised technical specification |
|--|-----------------------|------------------------------------|
| Reaction to fire                       | A2-s1, d0             |                                    |
| Release of dangerous substance, for:   |                       |                                    |
| - Cadmium                              | < 0,01 mg/l           |                                    |
| - Lead                                 | < 0,1 mg/l            |                                    |
| Breaking strength                      | > 1300 N              |                                    |
| Slipperiness                           | NPD                   |                                    |
| Tactility                              | NPD                   | BS EN 14411:2012                   |
| Bond strength/adhesion, for:           |                       |                                    |
| Cementitious adhesive, type C2         | > 1 N/mm <sup>2</sup> |                                    |
| Thermal shock resistance               | Pass                  |                                    |
| Durability for:                        |                       |                                    |
| - internal use:                        | Pass                  |                                    |
| - external use: freeze-thaw resistance | Pass                  |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2023

Place and date of issue

TAU CERAMICA SOLUTIONS, S.L.U. CUrarrica CI B-12958112 Castignaturell, no 18 12200 ONDA (CASTELLON) SPAIN





Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with low water absorption E<sub>b</sub> ≤0,5 % with thickness < 7,5 mm, meshed.</p>

2. Intended use(s)

# For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

## TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 3 and 4

Name and identification number of notified laboratory, if relevant – not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

#### 6. Declared performances

| Essential characteristics              | Performance           | Harmonised technical specification |
|--|-----------------------|------------------------------------|
| Reaction to fire                       | A2-s1, d0             |                                    |
| Release of dangerous substance, for:   |                       |                                    |
| - Cadmium                              | < 0,01 mg/l           |                                    |
| - Lead                                 | < 0,1 mg/l            |                                    |
| Breaking strength                      | > 700 N               |                                    |
| Slipperiness                           | NPD                   |                                    |
| Tactility                              | NPD                   | BS EN 14411:2012                   |
| Bond strength/adhesion, for:           |                       |                                    |
| Cementitious adhesive, type C2         | > 1 N/mm <sup>2</sup> |                                    |
| Thermal shock resistance               | Pass                  |                                    |
| Durability for:                        |                       |                                    |
| - internal use:                        | Pass                  |                                    |
| - external use: freeze-thaw resistance | Pass                  |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2023 Place and date of issue TAU CERAMICA SOLUTIONS, S.L.U. CIF B-12958112 Calle Del Toll, nº 18 12200 ONDA (CASTELLÓN) SPAIN





Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with low water absorption E<sub>b</sub> ≤0,5 % with thickness ≥ 7,5 mm

2. Intended use(s)

## For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

# TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 3 and 4

Name and identification number of notified laboratory, if relevant – not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

# 6. Declared performances

| Essential characteristics              | Performance           | Harmonised technical specification |
|--|-----------------------|------------------------------------|
| Reaction to fire                       | A1 <sub>FL</sub> /A1  |                                    |
| Release of dangerous substance, for:   |                       |                                    |
| - Cadmium                              | < 0,01 mg/l           |                                    |
| - Lead                                 | < 0,1 mg/l            |                                    |
| Breaking strength                      | > 1300 N              |                                    |
| Slipperiness                           | NPD                   |                                    |
| Tactility                              | NPD                   | BS EN 14411:2012                   |
| Bond strength/adhesion, for:           |                       |                                    |
| Cementitious adhesive, type C2 E S2    | > 1 N/mm <sup>2</sup> |                                    |
| Thermal shock resistance               | Pass                  |                                    |
| Durability for:                        |                       |                                    |
| - internal use:                        | Pass                  |                                    |
| - external use: freeze-thaw resistance | Pass                  |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2023 Place and date of issue

Signature